

Interior Paint

| | |
|----------------------------|---|
| DESCRIPTION | Full-matt low-odour waterborne acrylate latex paint for use on interior walls and ceilings. Feelings Interior Paint has exceptional resistance to washing using mild non-abrasive cleaning materials. |
| EXAMPLES OF USE | Plaster, concrete, brick, building blocks and boards, MDF, wallpaper, etc. Feelings Interior Paint can be used for repainting interior surfaces previously coated with waterborne or alkyd paints. Feelings Interior Paint is also the recommended base coat for Feelings Effect Paint |
| TECHNICAL DATA | Solids volume: approx. 35% Density: approx. 1.3 kg/l Scrub resistance: >5000 cycles (DIN 53778) Heat resistance: 85°C (ISO 3248) Base paints: A and C Finnish Emission Classification: M1 VOC Statistics: 30g/l(2010) |
| COLOUR RANGE | Available in white, Feelings Interior Colour Range and the complete Tikkurila Symphony Colour Collection. Also available in BS 4800, NCS, RAL and most other colour ranges. |
| PREPARATION | Surfaces must be clean, dry, and free from grease, dirt, oil, wax, rust, all loose material and surface contamination. Use recommended Tikkurila products as cleaning agents and for mould removal. Use recommended Tikkurila fillers for filling cracks, nail holes, blemishes, etc., and levelling of uneven surfaces. Ensure that existing glossy, gloss painted and filled surfaces are thoroughly flatted down. Ensure that all surfaces are thoroughly prepared. Spot prime all bare areas on previously painted surfaces with Feelings Interior Paint. |
| APPLICATION | Methods: brush, roller or spray application. For airless spray use a 0.018"- 0.023" spray tip. Thinning: if necessary thin by up to 5% with water. |
| PAINTING CONDITIONS | All surfaces to be painted must be dry, the temperature of the air at least +5°C and the relative humidity of the air below 80%. |
| PAINTING | Stir the paint thoroughly and apply two coats of Feelings Interior Paint overall. |
| COVERAGE | 10-12 m ² /l per coat. The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method. |
| DRYING TIMES | At 23°C and 50% relative humidity of the air: normally touch-dry in ½ hour and recoatable after 1-2 hours. |

CLEANING OF TOOLS

Clean with water immediately after use.

ENVIRONMENTAL

Empty cans should be recycled or disposed of in accordance with local regulations.
Liquid waste should be destroyed according to the local regulations.

**HEALTH AND SAFETY
CLASSIFICATION**

EC Directive 99/45/EC. Not classified as hazardous to health.
Handle with care, avoid prolonged contact with skin and breathing of spray mist.

A Material Safety Data Sheet is available on request.

STORAGE AND TRANSPORT

Protect from frost.

ADR/RID -

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.