

Extra Durable Paint

DESCRIPTION	Semi-matt or semi-gloss, low-odour, mould resistant waterborne acrylate latex finishing paint for use on interior walls and ceilings. Particularly suitable for humid rooms and areas which require frequent washing down with strong detergents and disinfectants eg. kitchens, bathrooms, shower rooms, utility rooms, swimming pool areas etc.
EXAMPLES OF USE	Plaster, concrete, brick, building block and boards, MDF, etc. Feelings Extra Durable can be used on primed wood, metal, and for repainting interior surfaces previously coated with waterborne, alkyd or acid catalysed paints.
TECHNICAL DATA	<p>Solids volume: approx. 36%</p> <p>Density: approx. 1.2 kg/l</p> <p>Scrub resistance: >10 000 cycles (DIN 53778)</p> <p>Chemical resistance: Good (ISO 2812-1)</p> <p>Heat resistance: 70°C (ISO 3248)</p> <p>Base paints: A and C</p> <p>Classification of Finishing Materials: M1</p> <p>VOC Statistics: 30g/l(2010)</p>
COLOUR RANGE	Available in white, Feelings Interior Colour Range and the complete Tikkurila Symphony Colour Collection. Also available in BS 4800, NCS, RAL and most other colour ranges.
PREPARATION	Surfaces must be clean, dry, and free from grease, dirt, oil, wax, rust, all loose material and surface contamination. Use recommended Tikkurila products as cleaning agents and for mould removal. Use recommended Tikkurila fillers for filling cracks, nail holes, blemishes etc., and levelling of uneven surfaces. Ensure that existing glossy, gloss painted and filled surfaces are thoroughly flatted down. Ensure that all surfaces are thoroughly prepared.
PRIMING	<p>Prime unpainted wall and ceiling surfaces overall and spot prime all bare areas on previously painted walls and ceilings with Feelings Universal Primer.</p> <p>Prime all bare wood with Otex/Unica Adhesion Primer and bare metal surfaces with Unica Metal Primer.</p> <p>In areas of high humidity walls and ceilings should be primed with Feelings Moisture Stop prior to the application of Feelings Extra Durable.</p>
APPLICATION	<p>Methods: brush, roller or spray application.</p> <p>Thinning: if necessary thin by up to 5% with water.</p>
PAINTING CONDITIONS	All surfaces must be dry, the temperature of the air at least +5°C, and the relative humidity of the air below 80%.
PAINTING	Stir the paint thoroughly and apply two coats of Feelings Extra Durable overall.

COVERAGE

7-10 m²/l per coat.

The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.

DRYING TIMES

At 23°C and relative humidity of the air below 50%: normally touch-dry in two hours and recoatable after four hours. Final hardness will be achieved after 2-3 days.

CLEANING OF TOOLS

Clean with water immediately after use.

ENVIRONMENTAL

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.

HEALTH AND SAFETY CLASSIFICATION

EC Directive 99/45/EC. Not classified as hazardous to health.

Handle with care, avoid prolonged contact with skin and breathing of spray mist. Use the product safely. Always read the label and product information before use.

A Material Safety Data Sheet is available on request.

STORAGE AND TRANSPORT

Protect from frost.

ADR/RID -

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.