liquid imagination by VALTTI

Furniture Paint

DESCRIPTION	Semi-matt or gloss, low-odour, non-yellowing, waterborne acrylate latex finishing paint for use on interior substrates. Feelings Furniture Paint can be used on a wide range of interior surfaces, and dries to an attractive finish which is hard wearing and easily cleaned.
EXAMPLES OF USE	Interior wood panelling, doors, skirting, architraves, furniture, cabinets, walls, MDF, radiators etc. Feelings Furniture Paint can also be used on primed metal and for repainting interior surfaces previously coated with waterborne, alkyd or acid catalysed paints.
TECHNICAL DATA	Solids volume: approx. 33% Density: approx. 1.2 kg/l Scrub resistance: >5000 cycles (DIN 53778) Chemical resistance: Good (ISO 2812-1) Heat resistance: 85°C (ISO 3248) Base paints: A and C Classification of Finishing Materials: M1 VOC Statistics: (cat A/d) 160g/l(2010) Feelings Furniture Paint contains VOC max. 130g/l
COLOUR RANGE	Available in white, Feelings Interior Colour Range and the complete Tikkurila Symphony Colour Collection. Also available in BS 4800, NCS, RAL and most other colour ranges.
PREPARATION	Surfaces must be clean, dry, and free from grease, dirt, oil, wax, rust, all loose material and surface contamination. Use recommended Tikkurila products as cleaning agents and for mould removal. Treat knots and resinous areas with Tikkurila Knotting Lacquer. Use recommended Tikkurila fillers for filling cracks, nail holes, blemishes, etc., and levelling of uneven surfaces. Ensure that existing glossy, gloss painted and filled surfaces are thoroughly flatted down. Ensure that all surfaces are thoroughly prepared prior to priming and painting. Note: Discoloration of paint, especially noticeable within light colours, may occur over knots and resinous areas present in the wood. Particular attention with regards to preparation should be given to wood such as oak, teak, cedar, douglas fir, mahogany and idigbo, etc., which contain oil and water-soluble tannin which may impair the drying, hardening or adhesion of surface coatings and discolour the finished surface.
PRIMING	Prime bare interior wood overall and, if necessary, spot prime all bare areas on previously painted surfaces with Feelings Furniture Primer or Otex / Unica Adhesion Primer. Otex/Unica Adhesion Primer is preferable on wood that contains substances which may 'bleed through' and cause staining to the finished surface. Prime all bare metal and potential rust spots with Unica Metal Primer.
APPLICATION	Methods: brush, roller or spray application. Polyester and nylon paint brushes are best suited for the application of Feelings Furniture Paint. For airless spray use a 0.013"- 0.015" spray tip. Thinning: if necessary thin by up to 5% with water.

liquid imagination by VALTTI

PAINTING CONDITIONS	All surfaces to be painted must be dry, the moisture content of the wood below 20%, the temperature of the air at least +8°C, and the relative humidity of the air below 80%.
PAINTING	Stir the paint thoroughly and apply two coats of Feelings Furniture Paint overall.
COVERAGE	8-10 m^2/l per coat. The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.
DRYING TIMES	At 23°C and 50% relative humidity of the air: normally touch-dry in 1 hour and recoatable after 16 hours. Final hardness will be achieved after 2-3 days.
CLEANING OF TOOLS	Clean with water immediately after use.
ENVIRONMENTAL	Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.
HEALTH AND SAFETY CLASSIFICATION	EC Directive 99/45/EC. Not classified as hazardous to health. Handle with care, avoid prolonged contact with skin and breathing of spray mist. A Material Safety Data Sheet is available on request.
STORAGE AND TRANSPORT	Protect from frost. ADR/RID -

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.