

Furniture Primer

DESCRIPTION	Matt finish, low-odour waterborne acrylate primer for use on interior substrates. Offers good adhesion, opacity and grain-filling properties, and provides a first-class foundation for subsequent coats of Feelings Furniture Paint.
EXAMPLES OF USE	Interior wood panelling, doors, skirting, architraves, furniture, cabinets, walls, MDF, etc. Feelings Furniture Primer can be used for repainting interior surfaces previously coated with waterborne, alkyd or acid catalysed paints.
TECHNICAL DATA	Solids volume: approx. 35% Density: approx. 1.3 kg/l Base paints: A and C Classification of Finishing Materials: M1 VOC Statistics: (cat A/g) 30g/l(2010) Feelings Furniture Primer contains VOC max. 30g/l
COLOUR RANGE	Available in white, Feelings Interior Colour Range and the complete Tikkurila Symphony Colour Collection. Also available in BS 4800, NCS, RAL, NCS and most other colour ranges.
PREPARATION	Surfaces must be clean, dry, and free from grease, dirt, oil, wax, rust, all loose material and surface contamination. Use recommended Tikkurila products as cleaning agents and for mould removal. Treat knots and resinous areas with Tikkurila Knotting Lacquer. Use recommended Tikkurila fillers for filling cracks, nail holes, blemishes, etc., and levelling of uneven surfaces. Ensure that existing glossy, gloss painted and filled surfaces are thoroughly flatted down. Ensure that all surfaces are thoroughly prepared. <u>Note:</u> Discoloration of paint, especially noticeable within light colours, may occur over knots and resinous areas present in the wood. Particular attention with regards to preparation should be given to wood such as oak, teak, cedar, douglas fir, mahogany and idigbo, etc., which contain oil and water-soluble tannin which may impair the drying, hardening or adhesion of surface coatings and discolour the finished surface. After thorough degreasing, the use of Otex/Unica Adhesion Primer is preferable on these types of timbers. Prime all metal and potential rust spots with Unica Metal Primer.
APPLICATION	Methods: brush, roller or spray application. Polyester and nylon paint brushes are best suited for the application of Feelings Furniture Primer. For airless spray use a 0.013"-0.015" spray tip. Thinning: if necessary thin by up to 10% with water.
PAINTING CONDITIONS	All surfaces to be painted must be dry, the moisture content of the wood below 20%, the temperature of the air at least +8°C, and the relative humidity of the air below 80%.
PAINTING	Stir the paint thoroughly. Prime unpainted surfaces overall and spot prime all bare areas on previously painted surfaces with Feelings Furniture Primer. Prime absorbent surfaces with Feelings Furniture Primer thinned by up to 10% with water, allow to dry and apply a further coat unthinned.

COVERAGE

6-8 m²/l per coat.

The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.

DRYING TIMES

At 23°C and 50% relative humidity of the air: normally touch-dry in one hour and recoatable after 4 hours.

CLEANING OF TOOLS

Clean with water immediately after use.

ENVIRONMENTAL

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.

HEALTH AND SAFETY CLASSIFICATION

EC Directive 99/45/EC. Not classified as hazardous to health.

Handle with care, avoid prolonged contact with skin and breathing of spray mist.

A Material Safety Data Sheet is available on request.

STORAGE AND TRANSPORT

Protect from frost.

ADR/RID -

The above information, based on laboratory tests and practical experience, has been proved valid at the date marked on the product data sheet. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As a manufacturer we cannot be responsible for any damages caused by using the product against our instructions or for inappropriate purposes.